WHAT IS CLAIMED IS

1.	A device for selecting a coding mode for a video encoding system, comprising:

a first memory for storing frame data of an input image;

a second memory for storing the previous frame data;

5	a motion prediction part for comparing the present input frame data stored in the first memory with the previous frame data stored in the second memory to detect a SAD (sum of absolute pixel differences) value; and

an SAD examiner for generating coding selection information for 10	coding the frame data in an intra-coding mode when the SAD value of the input frame data output from the motion prediction part exceeds a predetermined SAD threshold, or in an inter-coding mode when the SAD value of the input frame data does not exceed the predetermined SAD threshold.

2.	A coding mode selecting method in which an SAD value between input frames is used in a video encoding system, the coding mode selecting method comprising the steps of:

detecting the SAD value of input frame data;

5	determining whether the detected SAD value exceeds a predetermined SAD threshold;

9

coding the input frame in an intra-coding mode when the SAD
value of the input frame exceeds the SAD threshold; and

coding the input frame in an inter-coding mode when the SAD
10   value of the input frame does not exceed the SAD threshold.

3.   A device for selecting a coding mode for a video
encoding system, comprising:

a motion prediction part for comparing data of a present input
frame with data of a previous frame to detect a SAD (sum of absolute
5   pixel differences) value; and

an SAD examiner for generating coding selection information for
coding the frame data in an intra-coding mode when the SAD value of
the input frame data output from the motion prediction part exceeds a
predetermined SAD threshold, or in an inter-coding mode when the
10   SAD value of the input frame data does not exceed the predetermined
SAD threshold.